

WHAT IS CLAIMED IS:

Subs  
AT

1. An optical space transmitter comprising:  
a light source for emitting a light beam modulated  
according to a signal to be transmitted;  
an optical system for sending out the light beam  
emitted from said light source as transmission light  
beam with an angle of expansion;

a temperature detector for detecting the internal  
temperature of the device; and

a control means for changing the angle of  
expansion of said transmission light beam as a function  
of the temperature detected by said temperature  
detector.

2. An optical space transmitter according to  
claim 1, wherein

said control means includes an computing circuit  
for determining by computation an appropriate angle of  
expansion of the light beam to be transmitted on the  
basis of the temperature detected by said temperature  
detector and a drive means for driving at least part of  
said optical system in the direction of the optical  
axis according to the outcome of the computation of the  
computing circuit.

3. An optical space transmitter according to  
claim 1, further comprising:

a light receiving means for converting the reception signal transmitted from another device and taken into the own device so as to make the optical axis thereof agree with the optical axis of the light beam to be transmitted into an electric signal.

4. An optical space transmitter according to claim 3, further comprising:

an angle correcting means for correcting the angular displacement between the light beam to be transmitted and the received light beam.

5. An optical space transmitter according to claim 4, wherein

said angle correcting means has a tracking mirror arranged on the optical path of the light beam to be transmitted and the received light beam and an actuator for changing the angle of the tracking mirror.

6. An optical space transmitter according to claim 5, wherein

said optical system includes a beam splitter for separating the received light beam from the light beam to be transmitted and a half mirror for dividing the received light beam separated by the beam splitter into two light beams and said light receiving means includes a first photodetector for receiving one of the two

Subs  
a7

SAS  
a7  
cl

light beams produced by said half mirror by dividing the incoming light beam and detecting it as main signal and a second photodetector for receiving the other light beam and detecting the angular displacement between the light beam to be transmitted and the received light beam, said actuator being adapted to change the angle of the tracking mirror according to the output signal of said second photodetector.

5

add a7